

3DP 65-125/4.0

Performance Curve

Pump Name

3DP 65-125/4.0

Customer	Date	09.06.2024	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID		E-mail

Requested data


1	Flow	m³/h	
2	Head	m	
3	Geodetic head	m	

Pump

Operating flow	m³/h		Frequency	Hz	50
Operating head	m		Number of poles		2
Impeller diameter designed	mm	128	Speed	rpm	2900

Test standard: ISO 9906:2012 - Grade3B


Water; 20°C; 998.3kg/m³; 1cSt



Dimensions

Pump Name 3DP 65-125/4.0

Customer	Date 09.06.2024	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail



Dimensions in mm								
1	A	263	H2	180				
2	B	851	H3	171				
3	B1	388	N1	350				
4	D	80	N2	390				
5	Dia D1	200	N3	300				
6	Dia D2	185	R	100				
7	Dia DN1	80	S1	22				
8	Dia DN2	65	S2	20				
9	Dia K1	160	T	750				
10	Dia K2	145	V1	M25x1,5				
11	Dia P1	138	V2	M20x1,5				
12	Dia P2	122	Weight P&M	70.9 kg				
13	E	590						
14	H	390						
15	H1	160						


(1/3)

Construction

Pump Name

3DP 65-125/4.0

Customer	Date09.06.2024	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail



(2/3)

Construction

Pump Name 3DP 65-125/4.0

Customer	Date 09.06.2024	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

N°	PART NAME	MATERIAL	DIMENSIONS	STANDARD	Q.TY
1	Casing	Cast iron EN-GJL-200-EN 1561			1
3	Support	Cast iron EN-GJL-200-EN 1561			1
4	Casing cover	EN 1.4301 (AISI 304)			1
6	Shaft - Wet extension	EN 1.4301 (AISI 304)			1
6A	Flexible coupling	Cast iron EN-GJL-250-EN 1561			1
7	Impeller [1]	-			1
11	Mechanical seal [2]	-			1
12	Motor	-			1
19	Bearing	-			1
20	Bearing	-			1
24	Priming plug	Brass	G 3/8" L=8	DIN 906	1
25	Draing plug	Brass	G 3/8" L=8	DIN 906	1
26	O-ring 32-125, 40-125 32-160, 40-160, 50-125, 65-125 32-200, 40-200, 50-160, 50-200, 65-160, 65-200 [3]	NBR/FPM/EPDM	158.11x5.34 183.52x5.34 227.96x5.34	OR 6625 OR 6720 OR 6895	1
32	Key Up to 11 kW 50-200/15 15 kW and above	EN 1.4401 (AISI 316)	6x6x25 8x7x30	UNI 6604	1
33	Key	C 40	8x7x40	UNI 6604	1
34	Impeller nut Up to 11kW 50-200/15 15 kW and above	EN 1.4301 (AISI 304)	M16x1.5 M18x1.5 M20x1.5	UNI 7474	1
42	Pump support	Fe 37 Galvanized		EBARA DRAWING	1
42A	Base	Fe 37 Galvanized			1
44	Protection	Fe 37 Galvanized			1
50	Foot	Aluminium / Galvanized steel			1
58	Cable gland	-			1
66	Impeller side bearing cover	Cast iron EN-GJL-200-EN 1561			1
67	Motor side bearing cover	Cast iron EN-GJL-200-EN 1561			1
72	Casing ring [4]	EN 1.4301 (AISI 304)			1
75	Washer	Aluminum	22x17x1.5	EBARA DRAWING	1
76	Washer	Aluminum	22x17x1.5	EBARA DRAWING	1
92	"V" ring	-	VS - 0030		1
93	"V" ring	-	VS - 0030		1
200	Screw 32-125, 40-125 32-160, 40-160, 50-125, 65-125 32-200, 40-200, 50-160 50-200, 65-160, 65-200	Gv. Steel 8.8 strenght class ISO 898-1	M 8x30 M 10x35	UNI 5739	8 10 12
235	Washer 32-125, 40-125 32-160, 40-160, 50-125, 65-125 32-200, 40-200, 50-160 50-200, 65-160, 65-200	Galvanized Steel	8.4x17 10.5x21	UNI 6592	8 10 12

[1] EN 1.4301 (AISI 304) for 32, 40, 50 series;
EN 1.4401 (AISI 316) for 65 series

[2] See **CONSTRUCTION 3**

[3] See **CONSTRUCTION 3**, "O-ring" column

[4] Only for: 32-200, 40-200, 50-160, 50-200


(3/3)

Construction

Pump Name

3DP 65-125/4.0

Customer	Date09.06.2024	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail



Pump type	Dimensions [mm]								Material			
	d1	d2	d3	d4	d5	L	L1	L2	A Rotary seal ring	Standard B Stationary seal ring	C O-ring	D Frame + Spring
32-125/160/200 40-125/160/200 50-125/160/200 65-125 65-160/7.5-9.2-11	22	19	38	31	37	37.5	27.5	10	Ceramic	Carbon	NBR	EN 1.4301 (AISI 304)