

Technical Data

Pump Name

LPC4 80-200/2.26 QQPFF

Customer	Date 2024-07-02	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID Proiect redenumit 2024-07-02 22:34:28	E-mail

Requested data

1	Pump type	CENTRIFUGAL PUMPS	Fluid	Water
2	Number of pumps / Reserve	1 / 0	Liquid temperature °C	20
3	Flow m³/h		Kin. viscosity mm²/s	1.005
4	Head m		Vapour pressure bar	0.0234
5	Geodetic head m		PH value	
6	Inlet pressure (pin) bar	0	Density kg/m³	998.3
7	Available system NPSH		Solids Weight %	0
8	Ambient temperature °C	20		

Pump

9	Pump Name	LPC4 80-200/2.26 QQPFF	Frequency Hz	60
10	Design	CENTRIFUGAL PUMPS	Installation type	STANDARD
11	Manufacturer	EBARA	Impeller Diameter	Max. mm 165
12	Speed rpm	1750		Designed mm 165
13	No. of Stage	1		Min. mm 165
14	Connection Suction side		Flow	Operating m³/h
15	Connection Discharge side			Max- m³/h 66
16	Max Working Pressure bar	10		Min- m³/h 15
17	Shut-off head bar	1.23	Head	Operating m
18	Total weight kg	See the table of "Dimensions".		- (Qmax.) m 8.5
19	Shaft power kW			- (Qmin.) m 12.6
20			Max. Shaft Power at max. impeller kW	2.19
21	Required pump NPSH m		Efficiency %	

Materials

22	Impeller	EN-GJL-200		
23	Intermediate casing	EN-GJL-200		
24	Bottom casing	EN-GJL-200		
25	Shaft	Stainless steel		
26	Gasket	AF1600		
27				

Motor

28	Manufacturer	LAFERT	Insulation class	F
29	Type	TEFC_LPC4 80-200/2.26_265_Three Phase	Phases	3~
30	Specific design	IE2 / 60 Hz / Pole pairs 2	Frame size	100
31	Rated power kW	2.2	Weight kg	19.5
32	Number of poles	4	Electric voltage V	265
33	Speed rpm	1728	Electric current A	7.2
34	Degree of protection	IP 55		
35				

Remarks

Performance Curve

Pump Name

LPC4 80-200/2.26 QQPFF

Customer	Date	2024-07-02	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Project redenumit 2024-07-02 22:34:28	E-mail


Requested data

1	Flow	m³/h		Operating flow	m³/h		Frequency	Hz	60
2	Head	m		Operating head	m		Number of poles		4
3	Geodetic head	m		Impeller diameter designed	mm	165	Speed	rpm	1750

Pump

Test standard: ISO 9906:2012 - Grade3B


Water; 20°C; 998.3kg/m³; 1mm²/s



Dimensions

Pump name LPC4 80-200/2.26 QQPFF

Customer	Date	2024-07-02	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Proiect redenumit 2024-07-02 22:34:28	E-mail



Dimensions in mm							
1	A	580	L Weight P&M	24			
2	B	160		52,4 kg			
3	C	420					
4	D	301					
5	Dia A	160					
6	Dia B	138					
7	Dia D	200					
8	Dia DN	80					
9	Dia n	8					
10	Dia Z	18					
11	E	146					
12	F	155					
13	G	500					
14	H	275					
15	I	225					


(1/2)

Construction

Pump name

LPC4 80-200/2.26 QQPFF

Customer	Date2024-07-02	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project IDProject redenumit 2024-07-02 22:34:28	E-mail



N°	PART NAME	MATERIAL	Q.TY
1111	Pump casing	EN-GJL-200	1
1340	Latern-Cover	EN-GJL-200	1
2200	Impeller	EN-GJL-200	1
2540	Baffle	NB 70	1
2912	Impeller nut	6.8-ZN	1
4200	Mechanical seal	Sic/Sic/NBR/AISI 304	1
4590	Gasket	AF 1600	1
6515	Drain plug	EN-GJMB-350-10	1
6521	Vent valve	CW509L	1
6576.1	Hexagonal head screw	8.8-ZN	4
6576.2	Hexagonal head screw	8.8-ZN	8
6710	Key	C50	1
6855.1	Impeller washer	R40-ZN	1
6855.2	Washer	R40-ZN	8
8020	Motor		1


(2/2)

Construction

Pump name

LPC4 80-200/2.26 QQPFF

Customer	Date2024-07-02	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project IDProject redenumit 2024-07-02 22:34:28	E-mail



Ref.	Name	Material
A	Rotary seal ring	Carbon
B	Stationary seal ring	Silicon Carbide
C	Gasket	EPDM
D	Bellows	EPDM
E	Spring plate	AISI 304
F	Spring	AISI 304
G	Spring plate	AISI 304