

Technical Data

Pump Name

LPC 80-160/15R QQPFF

Customer	Date	2024-06-16	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Proiect redenumit 2024-06-16 15:45:44	E-mail

Requested data

1	Pump type	CENTRIFUGAL PUMPS	Fluid	Water
2	Number of pumps / Reserve	1 / 0	Liquid temperature °C	20
3	Flow m³/h		Kin. viscosity mm²/s	1.005
4	Head m		Vapour pressure bar	0.0234
5	Geodetic head m		PH value	
6	Inlet pressure (pin) bar	0	Density kg/m³	998.3
7	Available system NPSH		Solids Weight %	0
8	Ambient temperature °C	20		

Pump

9	Pump Name	LPC 80-160/15R QQPFF	Frequency Hz	50
10	Design	CENTRIFUGAL PUMPS	Installation type	STANDARD
11	Manufacturer	EBARA	Impeller Diameter	Max. mm 160
12	Speed rpm	2900		Designed mm 160
13	No. of Stage	1		Min. mm 160
14	Connection Suction side		Flow	Operating m³/h
15	Connection Discharge side			Max- m³/h 135
16	Max Working Pressure bar	10		Min- m³/h 25
17	Shut-off head bar	3.62	Head	Operating m
18	Total weight kg	See the table of "Dimensions".		- (Qmax.) m 19.0
19	Shaft power kW			- (Qmin.) m 36.4
20			Max. Shaft Power at max. impeller kW	11.10
21	Required pump NPSH m		Efficiency %	

Materials

22	Impeller	EN-GJL-200		
23	Intermediate casing	EN-GJL-200		
24	Bottom casing	EN-GJL-200		
25	Shaft	Stainless steel		
26	Gasket	AF1600		
27				

Motor

28	Manufacturer	LAFERT	Insulation class	F
29	Type	TEFC_LPC 80-160/15R_400_Three Phase	Phases	3~
30	Specific design	IE3 / 50 Hz / Pole pairs 1	Frame size	132
31	Rated power kW	15	Weight kg	68
32	Number of poles	2	Electric voltage V	400
33	Speed rpm	2915	Electric current A	26.8
34	Degree of protection	IP 55		
35				

Remarks

Performance Curve

Pump Name

LPC 80-160/15R QQPFF

Customer	Date	2024-06-16	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Project redenumit 2024-06-16 15:45:44	E-mail

Requested data


1	Flow	m³/h	
2	Head	m	
3	Geodetic head	m	

Pump

Operating flow	m³/h		Frequency	Hz	50
Operating head	m		Number of poles		2
Impeller diameter designed	mm	160	Speed	rpm	2900

Test standard: ISO 9906:2012 - Grade3B


Water; 20°C; 998.3kg/m³; 1mm²/s



Dimensions

Pump name LPC 80-160/15R QQPFF

Customer	Date	2024-06-16	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Proiect redenumit 2024-06-16 15:45:44	E-mail



Dimensions in mm							
1	A	770	L Weight P&M	24			
2	B	160		88 kg			
3	C	610					
4	D	325					
5	Dia A	160					
6	Dia B	138					
7	Dia D	200					
8	Dia DN	80					
9	Dia n	8					
10	Dia Z	18					
11	E	131					
12	F	194					
13	G	440					
14	H	240					
15	I	200					


(1/2)

Construction

Pump name

LPC 80-160/15R QQPFF

Customer	Date2024-06-16	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project IDProject redenunit 2024-06-16 15:45:44	E-mail



N°	PART NAME	MATERIAL	Q.TY
1111	Pump casing	EN-GJL-200	1
1340	Latern-Cover	EN-GJL-200	1
2200	Impeller	EN-GJL-200	1
2540	Baffle	NB 70	1
2912	Impeller nut	6.8-ZN	1
4200	Mechanical seal	Sic/Sic/NBR/AISI 304	1
4590	Gasket	AF 1600	1
6515	Drain plug	EN-GJMB-350-10	1
6521	Vent valve	CW509L	1
6576.1	Hexagonal head screw	8.8-ZN	4
6576.2	Hexagonal head screw	8.8-ZN	8
6710	Key	C50	1
6855.1	Impeller washer	R40-ZN	1
6855.2	Washer	R40-ZN	8
8020	Motor		1


(2/2)

Construction

Pump name

LPC 80-160/15R QQPFF

Customer	Date2024-06-16	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project IDProject redenumit 2024-06-16 15:45:44	E-mail



Ref.	Name	Material
A	Rotary seal ring	Carbon
B	Stationary seal ring	Silicon Carbide
C	Gasket	EPDM
D	Bellows	EPDM
E	Spring plate	AISI 304
F	Spring	AISI 304
G	Spring plate	AISI 304