

Technical data

Pump name (*See Product description)EVM32 8-0F6/30

Customer	Date	2024-07-01	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Project redenumit 2024-07-01 19:11:00	E-mail

Requested data

1	Pump type	VERTICAL MULTISTAGE PUMPS	Fluid	Water
2	Number of pumps / Reserve	1 / 0	Liquid temperature °C	20
3	Flow m³/h		Kin. viscosity mm²/s	1.005
4	Head m		Vapour pressure bar	0.0234
5	Geodetic head m		PH value	
6	Inlet pressure (pin) bar	0	Density kg/m³	998.3
7	Available system NPSH		Solids Weight %	0
8	Ambient temperature °C	20		

Pump

9	Pump name	(*See Product description)EVM32 8-0F6/30	Frequency		Hz	60
10	Design	VERTICAL MULTISTAGE PUMPS	Installation type			Round flange
11	Manufacturer	EBARA	Impeller Diameter	Max.	mm	-
12	Speed rpm	3540		Designed	mm	
13	No. of Stage	8		Min.	mm	-
14	Connection Suction side		Flow	Operating	m³/h	
15	Connection Discharge side			Max-	m³/h	48
16	Max Working Pressure bar	30		Min-	m³/h	15
17	Shut-off head bar	26.54	Head	Operating	m	
18	Total weight kg	See the table of "Dimensions".		- (Qmax.)	m	127.2
19	Shaft power kW			- (Qmin.)	m	251.4
20			Max. Shaft Power at max. impeller		kW	25.68
21	Required pump NPSH m		Efficiency			%

Materials

22	Impeller	AISI 304		
23	Intermediate casing	AISI 304		
24	Bottom casing	ASTMCF8		
25	Shaft	AISI 316L		
26				
27				

Motor

28	Manufacturer	ATB	Insulation class	F
29	Type	TEFC_EVM32 8-0F6/30_380_Three Phase	Phases	3~
30	Specific design	IE3 / 60 Hz / Pole pairs 1	Frame size	200
31	Rated power kW	30	Weight kg	168
32	Number of poles	2	Electric voltage V	380
33	Speed rpm	3550	Electric current A	53.1
34	Degree of protection	IP 55		
35				

Remarks

Performance curve

Pump name (*See Product description)EVM32 8-0F6/30

Customer	Date	2024-07-01	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Project redenumit 2024-07-01 19:11:	E-mail

Requested data


1	Flow	m³/h	
2	Head	m	
3	Geodetic head	m	

Pump

Operating flow	m³/h		Impeller Diameter Designed	mm	
Operating head	m		Frequency	Hz	60
			Speed	rpm	3540

Test standard: ISO 9906:2012 - Grade3B


Water; 20°C; 998.3kg/m³; 1mm²/s



Dimensions

Pump name (*See Product description)EVM32 8-0F6/30

Customer	Date	2024-07-01	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Project redenumit 2024-07-01 19:11:46	E-mail



Dimensions in mm							
1	A	400					
2	B	354					
3	C	280					
4	H2	958					
5	H3	552					
6	SN	8					
7	Weight P&M	333 kg					
8							
9							
10							
11							
12							
13							
14							
15							


(1/4)

Construction

Pump name

(*See Product description)EVM32 8-0F6/30

Customer	Date2024-07-01	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project IDProject redenunit 2024-07-01 19:11:46	E-mail



Pump with double ball bearingm

(2/4)

Construction

Pump name (*See Product description)EVM32 8-0F6/30

Customer	Date	2024-07-01	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Proiect redenumit 2024-07-01 19:11:46	E-mail

N°	PART NAME	MATERIAL		DIMENSIONS	STANDARD
		EVM	EVML		
5-1	Suction casing	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
5-2	Intermediate Casing	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
5-3	Intermediate casing bearing	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
5-4	Discharge casing	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
6	Bottom casing	EN 1.4308 (ASTM CF8)	EN 1.4408 (ASTM CF8M)		
7	Outer casing	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
11	Casing cover	Cast iron+	Cast iron +		
21	Impeller	EN 1.4301 (AISI 304)	EN 1.4401 (AISI 316L)		
31	Shaft	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
39-1	Key	EN 1.4404 (AISI 316L)			
43-1	Shaft sleeve (mechanical seal)	Carbon Steel		12X8X90	UNI 6604
43-2	Shaft sleeve (intermediate)	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
43-3	Shaft sleeve (bearing)	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
43-4	Shaft sleeve (adjustment)	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
43-5	Shaft sleeve (last stage)	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
44-1	Shaft sleeve bearing	Tungsten carbide			
45	Flange holder	EN 1.402 (AISI 420)			
47	Ring Holder	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
48	Impeller nut	A2-70 UNI 7323 with inox insert	A4-70 UNI 7323 with inox insert	M16	
51	Motor adapter	Cast iron EN-GJL-200-EN 1561			
52-1	Bearing	Tungsten carbide			
56	Ball bearing	[1]			
70-1	Ring for bearing	EN 1.4301 (AISI 304)			
75	O-Ring (plug)	EPDM	FPM		
75-1	O-Ring (plug)	EPDM	FPM		
107	Liner ring	PTFE / EN 1.4301 (AISI 304) PTFE / EN 1.4404 (AISI 316L)			
111-1	Mechanical seal	[2]			
111-2	Mechanical seal cartridge	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
111-3	Mechanical seal seat	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
111-4	Seal holder	Brass OT 58 UNI 5705	EN 1.4404 (AISI 316L)		
115-1	O-Ring (outer casing)	EPDM	FPM	D.208.91 X5.34	
115-4	O-Ring (cartridge sleeve)	EPDM	FPM	D. 24.99X3.53	
115-5	O-Ring (seal cover)	EPDM	FPM	D.44.04X3.53	
120-1	Tie-rod	Galvanized steel 6.8 strenght class ISO 898/1			
120-3	Screw (mechanical seal)	A2-70 UNI 7323		M5X10	UNI 5731
120-4	Screw (casing cover)	Galvanized steel 8.8 strenght class ISO 898/1		M10X25	UNI 5793
120-5	Screw for coupling	EVM32 1 EVM32 3 to 10	Galvanized steel 8.8 strenght class ISO 898/1	M8X20 M10X30	UNI 5931 UNI 5739
120-6	Screw for coupling	EVM32 1 to 3-3 EVM32 3-0 to 10-3	Galvanized steel 8.8 strenght class ISO 898/1	M8X20 M12X30	UNI 5931 UNI 5931
120-7	Screw (bearing)	Galvanized steel 8.8 strenght class ISO 898/1		M6X10	UNI 5739
120-8	Screw (bearing housing)	EVM32 3-0 to 10-3 EVM32 2-0 to 3-3	Galvanized steel 8.8 strenght class ISO 898/1	M10X30 M12X25	UNI 5739 UNI 5739
120-10	Screw (base plate)	Galvanized steel 8.8 strenght class ISO 898/1		M12X40	UNI 5739
120-13	Screw for motor	EVM32 1 EVM32 2-0 to 3-3 EVM32 3-0 to 10-3	Galvanized steel 8.8 strenght class ISO 898/1	M8X20 M12X30 M16X65	UNI 5739 UNI 5739 UNI 5739
128-1	Nut for tie rod	Galvanized steel		M 16	UNI 5588
128-3	Nut (motor)	Galvanized steel		M16	UNI 5588
129	Lock nut	Carbon Steel			
130-1	Set screw	A2-70 UNI 7323		M6X8	UNI 5923
130-2	Screw for coupling guard	A2-70 UNI 7323		M5X6	UNI 7687
130-3	Set screw (mechanical seal)	A2-70 UNI 7323		M6X6	UNI 5923
130-4	Set screw (coupling pin)	Carbon steel		M 10X10	UNI 5923
131-1	Pin for shaft	Carbon Steel			
135-1	Washer (Tie rod)	Galvanized steel		17X30X3	UNI 6592
135-3	Washer (coupling)	Galvanized steel		10.5X17.5X2.2	UNI 1751
135-4	Washer (bearing)	Carbon steel		6.4	UNI 1751
136	Locking washer (coupling)	Carbon steel			
137-1	Impeller spacer	EN 1.4301 (AISI 304)	EN 1.4401 (AISI 316)		
140-1	Coupling (motor side)	Carbon steel			
140-2	Coupling (pump side)	Carbon steel			
160	Base	Cast iron EN-GJL-200-EN 1561			
162	Motor bracket	Cast iron EN-GJL-200-EN 1561			
212	Plug	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
212-1	Plug	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
245	Coupling guard	EN 1.4301 (AISI 304)			
273	Plug Washer	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
273-1	Plug Washer	EN 1.4301 (AISI 304)	EN 1.4404 (AISI 316L)		
274-1	C-type snap ring (mechanical seal)	EN 1.4301 (AISI 304)	EN 1.4401 (AISI 316)	Ø 26	UNI 7435
613	Flange	Carbon steel			

[1] See CONSTRUCTION 3

[2] See CONSTRUCTION 4

(3/4)

Construction

Pump name

(*See Product description)EVM32 8-0F6/30

Customer	Date2024-07-01	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project IDProject redenumit 2024-07-01 19:11:46	E-mail

Pump Type	N°																														
	5-2	5-3	11	21	21-1	39-1	43-2	43-3	43-4	44-1	51	52-1	56	70-1	107	111-5	120-4	120-5	120-7	120-8	128-3	129	135-3	135-4	136	140	140-1	140-2	150	274-2	274-3
EVM(L)32 7-0F6/30	5	1	1	7	/	1	5	1	1	1	1	1	1	1	7	1	4	4	3	4	4	1	4	3	1	/	1	1	/	/	/
EVM(L)32 8-3F6/30	6	1	1	5	3	1	6	1	1	1	1	1	1	1	8	1	4	4	3	4	4	1	4	3	1	/	1	1	/	/	/
EVM(L)32 8-0F6/30	6	1	1	8	/	1	6	1	1	1	1	1	1	1	8	/	4	4	3	4	4	1	4	3	1	/	1	1	/	/	/
EVM(L)32 9-3F6/30	7	1	1	6	3	1	7	1	1	1	1	1	1	1	9	/	4	4	3	4	4	1	4	3	1	/	1	1	/	/	/
EVM(L)32 9-0F6/30	7	1	1	9	/	1	7	1	1	1	1	1	1	1	9	/	4	4	3	4	4	1	4	3	1	/	1	1	/	/	/
EVM(L)32 10-4F6/30	7	2	1	6	4	1	7	2	2	2	1	2	1	1	10	/	4	4	3	4	4	1	4	3	1	/	1	1	/	/	/


(4/4)

Construction

Pump name

(*See Product description)EVM32 8-0F6/30

Customer	Date	2024-07-01	Company
Contact	Item no.		Issued by
Phone	Project		Phone
E-mail	Project ID	Project redenumit 2024-07-01 19:11:46	E-mail



Size [mm]	Max operating pressure [bar]	d [mm]	D1 [mm]	L [mm]	L1 [mm]	L2 [mm]	Material		
							1 Stationary Seal Ring	2 Rotary Seal Ring	3 Rubber
25	30	25	43	50	38.5	11.5	Carbon graphite	Silicon carbide	FPM