

AUTOTROL 368

CONTROL VALVE



FEATURES/BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Optical sensor for precision cycle positioning

Designed with double backwash for reduced hardness leakage

Continuous service flow rate of 16.6

GPM with a backwash of 2.75 GPM

Backwash capability accommodates softener tanks up to 10"

Super capacitor for keeping time of day during power outage

Programming stored in memory and will not be lost due to power outages

History data for valve performance

Designed for single tank systems only

External drain line flow control

Softener only control valve

OPTIONS

Plumbing connections in .75"-1.25" NPT, BSP, and sweat

Internal Autotrol* turbine

604- Simple economic electronic time clock control.

606- Simple economic electronic meter control.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.



UL recognized to the 979



TESTED EMC and Low Voltage Directive



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

Valve Body	Rubber	Glass-filled	Noryl
Components		Compounded for cold water	
Operating Pressure		20-125 PSI (1.38-8.61 bar)	
Water Temperature		35-100°F (2-38°C)	35-
Ambient Temperature		122°F (2-50°C)	0.14 gpm
Refill Flow Rate		(0.53 Lpm)/	
		0.33 gpm (1.25 Lpm)	

ELECTRICAL

Controller	
Operating Voltage	12 volt– AC
Input Supply Frequency	50 or 60 Hz
Moter Input Voltage	12 volt– AC
Controller System	
Power Consumption	3 watts average

TRANSFORMER- ALL CONTROLLERS

Transformer	
Output Voltage	12 volt– AC 400mA
Transformer	
Input Options	115 volt– AC 50/60 Hz
	230 volt– AC 50/60 Hz
	100 volt– AC 50/60 Hz
Transformer	
Plug Options	Indoor North American Plug
	Outdoor North American Plug
	Japanese Plug
	Taiwan/Korea Plug
	Australian Plug
	United Kingdown Plug
	Mainland Europe Plug

VALVE CONNECTIONS

Tank Thread	2-1/2" – 8, male
Inlet/Outlet	3/4" BSPT, male
	3/4" NPT, male
	1" BSPT, male
	1" NPT, male
Drain Line	1/2" – BSPT, male
	1/2" – NPT, male
Brine Line	3/8" – BSPT, male
	3/8" – NPT, male

DIMENSIONS

Riser Tube Dia.	1.05" (27 mm)
Riser Height	Flush to top of tank +/- 0.5"

FLOW RATE

Service	
5 psi (1.03 bar) drop	16.6 gpm (4.3Cv)
	3.77 m3/h (3.68kV)
Backwash	
25psi (1.72 Bar) drop	2.75 gpm (0.55Cv)
	0.62 m3/h (0.48kV)
Service	3.68 Kv
Backwash	0.48 Kv