



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 1 / 7

Pos.no	Description	Item no.
	Close-coupled pumps	
	Etabloc 150-125-400/3004 CC	05128039

Etabloc

Horizontal single-stage
volute casing pump in close-coupled design, with ratings to EN 733.
Axial suction nozzle, discharge nozzle pointing radially upwards.
Shaft fitted with a replaceable shaft sleeve in the shaft seal area.
Volute casing and casing cover with replaceable casing wear rings.
Volute casing with integrally cast pump feet for variants B, C and S.
Impeller matched to the operating point for saving energy.

Operating data

Water	Fluid handled	:
	Flow rate	:
	Head	:
20,00 °C	Fluid temperature	:
temperature	Permissible fluid	
0 bis +110	(min./max.)	:
pressure	Maximum operating	
	Ambient temperature:	-
10 to +50°C		



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 2 / 7

Pos.no	Description	Item no. (min./max.)	Qty.	UP / EUR	TP / EUR
		Motor/electronics			
	≥ 0,4	MEI value	:		
	30 kW	Motor rating	:		
	59,2 A	Max. rated current	:		
	500 1/min ... 1.800 1/min	Speed	:		
	3 x 380 V AC - 15 % to 480 V AC +10 %	Power supply	:		
	200L	Motor size	:		
		Energy efficiency class			
		: IE3 = Premium Efficiency			
	IP55	Enclosure	:		
	KSW - IEC	Motor make	:		
		Materials			
	CrNiMo steel 1.4408	Pump casing (102)	:		
	CrNiMo steel 1.4408	Impeller (230)	:		
		Pump shaft (210)	:		



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 3 / 7

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	A4/ AISI 316				
	CrNiMo steel 1.4571	Casing cover (161)	:		
	suction side (502.01): A4/ AISI 316	Casing wear ring,			
	discharge side (502.02): A4-70/ A193 Gr. B8M CL2	Casing wear ring,			
	Single mechanical seal with vented chamber (A-type cover)	Shaft seal type	:		
	:10 = Q1Q1X4GG	Shaft seal material			
	connections	Dimensions and			
	discharge nozzle DN2 : DN 125	Nominal size of			
	suction nozzle DN1 : DN 150	Nominal diameter of			
	suction side : 16	Nominal pressure,			
	discharge side : 16	Nominal pressure,			
	information	Purchase order			
	423,7 kg	Approx. net weight	:		
	KSB	Make	:		



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 4 / 7

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	Etabloc 150-125-400/3004 CC	Type	:		
	V3	Material price group	:		
	05128039	Material number	:		

Data sheet: technical data

Project name

Project ID

Customer

Contact

E-mail

Phone

Item-No.

Design

Type / Coding

Close-coupled pumps

Etabloc 150-125-400/3004 CC

Company


Contact

E-mail

Phone

2025-01-20

Page 5 / 7



demand data

Flow

Head

Geodetic head

Media

Liquid temperature

Concentration

Water

20 °C

100 %

Pump data

Make

Type

Design

Specific design

Max. fluid temperature

KSB

Etabloc 150-125-400/3004 CC

Close-coupled pumps

Single head pump

Hydraulic data (Duty point)

Flow

Head

Efficiency

Minimum Efficiency Index $\geq 0,4$

Material / sealing element

Volute casing

Shaft

Impeller

Impeller nut

Screw plug

Stud

CrNiMo steel 1.4408

CrNiMo steel 1.4571

CrNiMo steel 1.4408

A4/ AISI 316

A4/ AISI 316

A4-70/ A193 Gr. B8M CL2

Motor data

Power uptake

Rated power

Speed

Rated voltage

Rated current

Degree of protection

32,1 kW

30 kW

1.470 1/min

400 V

59,2 A

IP55

Product information

Ident. No./ type key

Weight loaded

Gross price

PL 2025-01-20


Price group

05128039

423,7 kg

56.519,26 EUR

V3



Data sheet: performance curve

Project name
Project ID

Item-No.

Design

Type / Coding

Close-coupled pumps

Etabloc 150-125-400/3004 CC

Customer

Contact

E-mail

Phone

Company

Contact

E-mail


Phone

2025-01-20

Page 6 / 7




Performance curve

Etabloc 150-125-400/3004 CC



Density 998,3 kg/m³

Viscosity 1,005 mm²/s



Name	Wert	Name	Wert
a	277 mm	l1	1.055 mm
a1	100 mm	m1	200 mm
b1	100 mm	m2	150 mm
d1	24 mm	m3	388 mm
d2	400 mm	m4	305 mm
d3	422 mm	n1	500 mm
DN1	150 mm	n2	400 mm
DN2	125 mm	n3	404 mm
h1	315 mm	n4	318 mm
h2	400 mm	p	309 mm
i	379 mm	s1	20 mm