

Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 1 / 8

Pos.no	Description	Item no.
	Close-coupled pumps	
	Etabloc PumpDrive 065-040-160/554	05128649
	GG	

Etabloc PumpDrive

Horizontal single-stage
volute casing pump in close-coupled design, with ratings to EN 733.
Axial suction nozzle, discharge nozzle pointing radially upwards.
Shaft fitted with a replaceable shaft sleeve in the shaft seal area.
Volute casing and casing cover with replaceable casing wear rings.
Volute casing with integrally cast pump feet for variants B, C and S.
Impeller matched to the operating point for saving energy.

PumpDrive 2 frequency

inverter

Self-cooling frequency inverter is mounted directly on the motor.
Controlled by integrated PI controller. Controlled variables are
pressure, differential pressure, flow rate, temperature. Display and
setting of all operating parameters via a control unit with graphical
display. Setpoint adjustment or control via external standard signal
or via the control unit. Protective function for drive and pump. Pump
and drive parameters pre-set at the factory.

Design:

Mains voltage	: 3~ 380 V AC -10 % to 480 V AC +10 %
Mains frequency	: 50 - 60 Hz ± 2 %
Internal power	: 24 V ± 10 %, max.
supply unit	600 mA DC
Enclosure	: IP55 (to EN 60529)
Ambient temperature	: -10 °C to +50 °C
Relative humidity in	: 5 % to 85 %, non-condensing
operation	
Service interface	: optical
Analog input	: 2 x 0/2 - 10 V or 0/4 - 20 mA
Analog output	: 1 x 0 - 10 V or 4 - 20 mA



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 2 / 8

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	Digital input	: 1 x hardware enable input, 5 x parameterisable			
	Relay output	: 2 changeover contacts, parameterisable			
	Bus systems (optional)	: Modbus RTU, Profibus DP, LON, BACnet MS/TP, Profinet			
	Operating data				
	Water	Fluid handled	:		
		Flow rate	:		
		Head	:		
	20,00 °C	Fluid temperature	:		
	temperature	Permissible fluid			
		(min./max.)	:		
	0 bis +110				
	pressure	Maximum operating			
	: ≤ 16 bar				
	10 to +50°C	Ambient temperature: -			
		(min./max.)			
	Motor/electronics				
	≥ 0,4	MEI value	:		
	5,5 kW	Motor rating	:		
		Max. rated current	:		



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 3 / 8

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	13,5 A				
	580 1/min ... 3.600 1/min	Speed	:		
	3 x 380 V AC - 15 % to 480 V AC +10 %	Power supply	:		
	132S	Motor size	:		
	: IE5	Energy efficiency class			
	IP55	Enclosure	:		
	KSB-Standard	Motor make	:		
		Materials			
	Grey cast iron JL1040	Pump casing (102)	:		
	Steel/tempered steel E335/C45	Impeller (230)	:		
	Grey cast iron JL1040	Pump shaft (210)	:		
	Grey cast iron JL1040	Casing cover (161)	:		
	Casing wear ring, suction side (502.01): DPAF seal plate, asbestos-free				
	Casing wear ring, discharge side (502.02): Grey cast iron GG / cast iron				
	Single mechanical seal with vented chamber (A-type cover)	Shaft seal type	:		

Page 4 / 8

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	:10 = Q1Q1X4GG	Shaft seal material			
	connections	Dimensions and			
		Nominal size of			
	discharge nozzle DN2 : DN 40				
		Nominal diameter of			
	suction nozzle DN1 : DN 65				
		Nominal pressure,			
	suction side : 16				
		Nominal pressure,			
	discharge side : 16				
	information	Purchase order			
		Approx. net weight :			
	85,67 kg				
		Make :			
	KSB				
		Type :			
	Etabloc PumpDrive 065-040-160/554 GG				
		Material price group :			
	V3				
		Material number :			
	05128649				



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 5 / 8

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	Frequency controller: PumpDrive2		1		

Data sheet: technical data

Project name

Project ID

Customer

Contact

E-mail

Phone

Item-No.

Design

Type / Coding

Close-coupled pumps

Etabloc PumpDrive 065-040-160/554 GG

Company


Contact

E-mail

Phone

2025-01-20

Page 6 / 8



demand data

Flow

Head

Geodetic head

Media

Liquid temperature

Concentration

Water

20 °C

100 %

Pump data

Make

Type

Design

Specific design

Max. fluid temperature

KSB

Etabloc PumpDrive 065-040-160/554 GG

Close-coupled pumps

Single head pump

Hydraulic data (Duty point)

Flow

Head

Efficiency

Minimum Efficiency Index $\geq 0,4$

Material / sealing element

Volute casing

Discharge cover

Shaft

Impeller

Bearing bracket lantern

Casing wear ring

Grey cast iron JL1040

Grey cast iron JL1040

Steel/tempered steel E335/C45

Grey cast iron JL1040

DPAF seal plate, asbestos-free

Grey cast iron GG / cast iron

Motor data

Power uptake

Rated power

Speed

Rated voltage

Rated current

Degree of protection

5,98 kW

5,5 kW

1.500 1/min

400 V

13,5 A

IP55

Product information

Ident. No./ type key

Weight loaded

Gross price

PL 2025-01-20



Price group

05128649

85,67 kg

11.524,64 EUR

V3



Data sheet: performance curve

Project name

Project ID

Item-No.

Design

Type / Coding

Close-coupled pumps

Etabloc PumpDrive 065-040-160/554 GG

Customer

Contact

E-mail

Phone

Company

Contact

E-mail


Phone

2025-01-20

Page 7 / 8


Performance curve

Etabloc PumpDrive 065-040-160/554 GG



Density 998,3 kg/m³

Viscosity 1,005 mm²/s



Name	Wert	Name	Wert
a	80 mm		
a1	119 mm		
DN1	65 mm		
DN2	40 mm		
h1	160 mm		
h2	160 mm		
h3	119 mm		
n1	225 mm		
n2	130 mm		
p	134 mm		
x	100 mm		