

Tender text

Project name
Project ID

Customer
 Contact
 E-mail
 Phone

Company
 Contact
 E-mail
 Phone

2025-01-20

Page 1 / 3

Pos.no	Description	Item no.
	Submersible dirty water motor pumps	
	AmaDrainer C 515 ND / 10	29128707
	AmaDrainer C 515 D / 10	
	Vertical single-stage fully floodable submersible motor pump in close-coupled design, IP68, without level control, max. immersion depth: 7 m.	
	<ul style="list-style-type: none"> - Connection socket or discharge elbow with internal thread - 10-metre power cable - Without float switch 	
	Operating data	
	Fluid handled	: Water
	Flow rate Q	:
	Head H	:
	Permissible fluid temperature	: 40 °C max. in continuous duty
	Drive	
	Supply voltage	: 3~ 400 / 50 Hz
	Frequency	: 50 Hz
	Nominal power P1	: 1,88 kW
	Motor rating P2	: 1,5 kW
	Nominal current	: 3,60 A
	Enclosure	: IP68
	Motor winding to	: IEC 60038
	Motor design to	: EN 60043 T1/IEC 34-1
	Thermal class	: F
	Starting method	: DOL
	Pump controlled via an external float switch, available as an accessory, and a switchgear / control unit	
	Materials	
	Pump casing	: Chromnickelstahl (1.4301)
	Suction cover	: Chromnickelstahl (1.4301)
	Impeller	: Polyamide (PA)
	Pump foot	: Polypropylen (PP)



Tender text

Project name

Project ID

Customer

Contact

E-mail

Phone

Company

Contact

E-mail

Phone

2025-01-20

Page 2 / 3

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	Rotor shaft	: Chrome steel (1.4021)			
	Dimensions				
	Free passage	: 10 mm			
	Discharge side	: DN 50			
	Length	: 300 mm			
	Width	: 280 mm			
	Height	: 440 mm			
	Purchase order information				
	Make	: KSB			
	Type series, size	: Ama-Drainer C 515 D / 10			
	Material price group	: 32			
	Weight	: 17,6 kg			
	Material number	: 29128707			

Data sheet: technical data

Project name
Project ID


Item-No.
Design Submersible dirty water motor pumps
Type / Coding AmaDrainer C 515 ND / 10

Customer
Contact
E-mail
Phone

Company
Contact
E-mail
Phone

2025-01-20

Page 3 / 3



demand data

Flow
Total head
Geodetic head
Media Water
Liquid temperature 20 °C

Pump data

Make KSB
Type AmaDrainer C 515 ND / 10
Design Submersible dirty water motor p
Specific design Single head pump
No. of pumps 1
Standby pump No
Max. fluid temperature 40 °C

Hydraulic data (Duty point)

Flow
Head

Material / sealing element

Pump casing Stainless steel 1.4401
Shaft CrNiMo steel 1.4571
Impeller
O-ring
Float switch

Dimensions

Discharge flange standard DN 50

Rated motor data

Power input (P1) 1,88 kW
Rated power (Pn) 1,5 kW
Speed 2.800 1/min
Rated voltage 400 V
Rated current (In) 3,6 A

Product information

Ident. No./ type key 29128707
Weight loaded 17,6 kg
Gross price 6.116,09 EUR
PL 2025-01-20
Price group 32