



Tender text

Project name
Project ID

Customer
Contact
E-mail
Phone

Company
Contact
E-mail
Phone

2025-01-20

Page 1 / 5

Pos.no	Description	Item no.
	Submersible dirty water motor pumps	
	Amarex D-max 80-230/038F4YSG	39110720
	Amarex KSB submersible motor pump for waste water applications, in grey cast iron and special materials	

Vertical submersible motor pump set for wet installation, single-stage, with three-phase motor to IEC standards. Temperature sensor for protection against overheating, optional leakage sensor in the motor space, power cable with resin-sealed, absolutely water-tight cable entry and service-friendly plug-type connection in the motor space.

Pump set:

Make : KSB
Impeller : Amarex D / 80-230
type : D-max open two-vane impeller

D-max is an open two-vane impeller of the latest generation. The D-max impeller ensures a non-clogging flow and an excellent hydraulic efficiency.

The D-flector technology is specially designed to drastically reduce the risk of clogging by items such as wet wipes contained in the waste water.

Impeller diameter : 230 mm
Free passage : 40 mm

Operating data:

Fluid handled : Water
Flow rate :
Head :
Power input : 400 V 3~
Operating temperature : 40 °C max.

Drive:

Nominal voltage : 3~400 V
Nominal frequency : 50 Hz
Starting method : DOL / star-delta starting is also

Tender text

Project name
Project ID

Customer
Contact
E-mail
Phone

Company
Contact
E-mail
Phone

2025-01-20

Page 2 / 5

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	possible Enclosure	: IP68 to EN 60529 / IEC 529, thermal class H			
	Explosion protection	: ATEX II 2G Ex db h IIB T4 Gb			
	Max. fluid temperature	: 40 °C			
	Thermal motor protection	: Temperature sensor			
	Leakage sensor in the motor space	: no			
	Efficiency class	:			
	Duty type	: S1 submerged / with motor section partly outside the fluid			
	Motor rating P2	: 3,9 kW			
	Motor rating P1	: 5,01 kW			
	Motor efficiency	: 77,8%			
	Nominal current	: 9,91 A			
	Speed	: 1.353 1/min			
	Cable length	: 10 m			
	Cable entry	: Screwed cable entry / cable entry with individually stripped, resin-embedded cores and service-friendly plug-type connection inside the motor			
	Materials:				
	Pump casing Class 35B)	: Grey cast iron EN-GJL-250 (A 48			
	Handle	: 1.4306			
	Impeller Class 35B)	: Grey cast iron EN-GJL-250 (A 48			
	Discharge cover 276 Type 420)	: Stainless steel EN-1.4021+QT800 (A			
	Suction cover	: D-flector			
	Shaft Class 35B)	: Grey cast iron EN-GJL-250 (A 48			
	Cable sheath	: Chloroprene rubber			
	Elastomer seals	: Nitrile-butadiene-rubber NBR			
	Coating	: Two-component epoxy resin High Solid			
	Colour	: RAL 5002			

Tender text

Project name
Project ID

Customer
Contact
E-mail
Phone

Company
Contact
E-mail
Phone

2025-01-20

Page 3 / 5

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	Shaft seal:				
	2 independent mechanical seals arranged in the oil reservoir				
	Pump end	:	Bellows-type mechanical seal		
	Motor end	:	Bellows-type mechanical seal,		
	Carbon-Al2O3				
	Oil fill	:	Environmentally friendly, non-toxic oil		
	Dimensions and connections:				
	Nominal size, discharge side	:	PN 16		
	Nominal size, suction side	:	DN 80		
	Pump weight	:	119 kg		
	Purchase order information:				
	Make	:	KSB		
	Type series / size	:	Amarex D 80-230		
	Material price group	:	18		
	Weight	:	119 kg		
	Item number	:	39110720		
	Motor: 394YSG			1	
	MOTOR				
	The motor shall be three-phase, dry squirrel-cage induction type in design conforming to IEC / VDE / EN standards. The motor shall be adequately sized and rated for continuous operation to maximum a fluid temperature of 40 °C (104 °F).				
	The motor housing shall be both air filled and w atertight. Motor protection shall be at minimum IP 68. Allow able maximum submergence shall be not less than 25 m.				
	The motor shall be rated for supply voltage of 400 V and frequency of 50 Hz and accept voltage fluctuations as per range A of DIN EN 60 034-1 (Supply voltage +/10 supply frequency -5%/+3%).				
	The motor shall be designed for a maximum of 30 number of starts per hour. Starting of the motor shall be direct.				
	The motor stator shall be wound to have an overall motor rating of 155°C, Class H. The rotor bars and short circuit rings shall be made of cast aluminum.				
	The motor and pump set complete shall be designed and manufactured by the same company.				
	MOTOR THERMAL PROTECTION				
	Temperature monitors shall be embedded in the motor windings for use in				



Tender text

Project name
Project ID

Customer
Contact
E-mail
Phone

Company
Contact
E-mail
Phone

2025-01-20

Page 4 / 5

Pos.no	Description	Item no.	Qty.	UP / EUR	TP / EUR
	<p>conjunction with and supplemental to external motor overload protection. These temperature sensitive switches shall allow for direct integration with the motor control circuit to shut down the pump if high temperatures are detected. The switches shall be normally closed rated for 250 V AC and a current of not less than 2 A. Additional temperature sensitive switches shall be embedded in the motor winding to limit temperatures of the motor as per explosion-proof certification. The pump's control shall shut down the pump should any of the monitors detect high temperature. Automatic reset shall not be allowed.</p> <p>MOTOR HOUSING MOISTURE PROTECTION A moisture detector shall be mounted in the motor's stator cavity allowing a control panel mounted relay to de-energize the motor when a leakage occurs.</p>				

Data sheet: technical data

Project name
Project ID


Item-No.
Design **Submersible dirty water motor pumps**
Type / Coding **Amarex D-max 80-230/038F4YSG**

Customer
Contact
E-mail
Phone

Company
Contact
E-mail
Phone

2025-01-20

Page 5 / 5



demand data

Flow
Total head
Geodetic head
Media Water
Liquid temperature 20 °C

Pump data

Make KSB
Type Amarex D-max 80-230/038F4YSG
Design Submersible dirty water motor p
Specific design Single head pump
No. of pumps 1
Standby pump No
Max. fluid temperature

Hydraulic data (Duty point)

Flow
Head

Material / sealing element

Casing Grey cast iron EN-GJL-250 (A 48 Class 35B)
Cover Grey cast iron EN-GJL-250 (A 48 Class 35B)
Suction cover D-flector
Suction cover material Ductile cast iron EN-GJS-600-3
Discharge cover Grey cast iron EN-GJL-250 (A 48 Class 35B)
Shaft Stainless steel EN-1.4021+QT800 (A 276 Type 420)
O-Rings Nitrile-butadiene-rubber NBR
Impeller Ductile cast iron EN-GJS-600-3

Dimensions

Discharge flange standard DN 80

Rated motor data

Power input (P1) 5,01 kW
Rated power (Pn) 3,9 kW
Speed 1.353 1/min
Rated voltage 400 V
Rated current (In) 9,91 A

Product information

Ident. No./ type key 39110720
Weight loaded 119 kg
Gross price 11.873,05 EUR
PL 2025-01-20
Price group

