

Technical data

High-pressure multistage centrifugal pump Helix FIRST V 208-5/25/E/S/400-50

Project ID

Untitled project 2025-03-03 15:12:38.853


Project name

Installation location


Customer pos. No.

Date 2025-03-03

Duty chart





ISO 9906: 2012 3B



Dimensions

H	700
H2	472
ØM	170
X	136
X	115

mm



Requested data

Flow	
Head	
Media	Water 100 %
Fluid temperature	20.00 °C
Density	998.30 kg/m³
Kin. viscosity	1.00 mm²/s

Hydraulic data (Duty point)

Flow	
Head	
Shaft power P2	
Hydraulic efficiency	
NPSH	

Product data

High-pressure multistage centrifugal pump	
Helix FIRST V 208-5/25/E/S/400-50	
Max. operating pressure	1,600 kPa
Inlet pressure max.	10 bar
Fluid temperature	-20 °C ... +120 °C
Max. ambient temperature	50 °C
Minimum efficiency index (MEI)	≥ 0.7

Motordata per Motor/Pump

Motor efficiency level	IE3
Mains connection	3~ 400 V / 50 Hz
Permitted voltage tolerance	+/-10 %
Max. speed	2,900 1/min
Rated power P2	0.75 kW
Rated current	1.70 A
Power factor	0.81
Service factor	1.15
Efficiency	76/79.7/80.7%
50% / 75% / 100%	
Degree of protection	IP55
Insulation class	F
Motor protection	No

Fitting dimensions

Pipe connection on the suction side	DN 25, PN 25
Pipe connection (pressure side)	DN 25, PN 25

Materials

Pump housing	5.1301/EN-GJL-250
Impeller	1.4307
Shaft	1.4301
Shaft seal	BQ7EGG
Gasket material	EPDM

Information for order placements

Weight approx.	33.8 kg
Item number	4201036