

Technical data

High-pressure multistage centrifugal pump HiMulti 3 H 50/2-23

Project ID

Untitled project 2025-03-03 15:12:38.853


Project name

Installation location

Customer pos. No.

Date 2025-03-03

Duty chart



Requested data

Flow	
Head	
Media	Water 100 %
Fluid temperature	20.00 °C
Density	998.30 kg/m^3
Kin. viscosity	1.00 mm^2/s

Hydraulic data (Duty point)

Flow
Head

Product data

High-pressure multistage centrifugal pump	
HiMulti 3 H 50/2-23	
Max. operating pressure	800 kPa
Inlet pressure max.	300 kPa
Fluid temperature	0 °C ... +40 °C
Max. ambient temperature	40 °C
Volume tank	50 l
Degree of protection	X4

Motordata per Motor/Pump

Mains connection	1~230 V / 50 Hz
Permitted voltage tolerance	+10/-15 %
Max. speed	2,900 1/min
Rated power P_2	0.40 kW
Rated current	2.70 A
0	

Insulation class	F
Motor protection	PTO

Fitting dimensions


Pipe connection on the suction side	G 1, PN 8
Pipe connection (pressure side)	Rp 1, PN 6/10

Materials

Impeller	PPE/PS-GF30
Motor housing	1.4034
Shaft seal	BVPFF
Stage chamber material	PPE/PS-GF30
Pump housing	PA6T/6I-GF40

Information for order placements

Weight approx.	17.8 kg
Item number	2549347



Dimensions

mm