

**Customer**


## Technical data

Glanded standard pump  
Atmos GIGA-N 80/160-5.5/4/6

Project ID                      Untitled project 2025-03-05 00:23:19.113

Project name  
Installation location  
Customer pos. No.

Date                      2025-03-05



**Requested data**

Flow  
Head  
Media                      Water 100 %  
Fluid temperature       20.00 °C  
Density                   998.30 kg/m<sup>3</sup>  
Kin. viscosity            1.00 mm<sup>2</sup>/s

**Hydraulic data (Duty point)**

Flow  
Head  
Shaft power  $P_2$   
Hydraulic efficiency  
NPSH  
Impeller size            180

**Product data**

Glanded standard pump  
Atmos GIGA-N 80/160-5.5/4/6  
Max. operating pressure   1,600 kPa  
Fluid temperature        -20 °C ... +140 °C  
Max. ambient temperature  40 °C  
Minimum efficiency index (MEI)  $\geq 0.4$

**Motordata per Motor/Pump**

Motor efficiency level     IE3  
Mains connection        3~ 380 V / 60 Hz  
Permitted voltage tolerance  $\pm 10 \%$   
Max. speed               1,765 1/min  
Rated power  $P_2$          5.50 kW  
Rated current            11.60 A  
Power factor             0.79  
Efficiency  
50% / 75% / 100%       89.4/91.5/91.7%  
Degree of protection     IP55  
Insulation class         F  
Motor protection         No

**Fitting dimensions**


Pipe connection on the suction side DN 100, PN 16  
Pipe connection (pressure side) DN 80, PN 16  
Port to Port

**Materials**

Pump housing             5.1301/EN-GJL-250  
  
Impeller                 EN-GJL-200  
Lantern                 5.1301/EN-GJL-250  
Shaft                    1.4021  
Shaft seal               AQ1EGG

**Information for order placements**

Weight approx.         201 kg  
Item number



**Dimensions**

mm

A	125	H	501	L3	1,030
B2	450	H2	225	L4	1,065
B3	400	H3	283	S1	220
DN1	DN 100, L	L	1,077	S4	24
DN2	DN 80, P	L2	185	X	140



Contact  
E-mail  
Phone

**Customer**

Contact  
E-mail  
Phone

## Hydraulic data

Glanded standard pump  
Atmos GIGA-N 80/160-5.5/4/6

Project ID: Untitled project 2025-03-05 00:23:19.113


Project name  
Installation location  
Customer pos. No.

Date: 2025-03-05

### Operating data

Rotational speed <b>1750 1/min</b>	Frequency <b>60 Hz</b>	Duty point <b>Q =</b>	<b>H =</b>	Suction port <b>DN 100</b>	Discharge port <b>DN 80</b>
---------------------------------------	---------------------------	--------------------------	------------	-------------------------------	--------------------------------

Power data referred to: Water; 20°C; 998.3kg/m³; 1.005mm²/s ±10 % tolerance with linear U/f frequency control



Pump curves in accordance with ISO 9906: 2012 3B

Contact  
E-mail  
Phone

**Customer**

Contact  
E-mail  
Phone

## Dimensions

Glanded standard pump  
Atmos GIGA-N 80/160-5.5/4/6

Project ID                      Untitled project 2025-03-05 00:23:19.113

Project name  
Installation location  
Customer pos. No.

Date                      2025-03-05



Coupling with spacer

Suction side                      DN 100, PN 16  
Discharge side                      DN 80, PN 16

**Dimensions**                      mm

Name	Value	Name	Value	Name	Value	Name	Value
A	125	H3	283	X	140		
B2	450	L	1,077				
B3	400	L2	185				
DN1	DN 100, PN 16	L3	1,030				
DN2	DN 80, PN 16	L4	1,065				
H	501	S1	220				
H2	225	S4	24				