

Customer


Technical data

Glanded standard pump Atmos GIGA-N 100/160-7.5/4/6

Project ID: Untitled project 2025-03-05 00:23:19.113

Project name
Installation location
Customer pos. No.

Date: 2025-03-05



Requested data

Flow
Head
Media: Water 100 %
Fluid temperature: 20.00 °C
Density: 998.30 kg/m³
Kin. viscosity: 1.00 mm²/s

Hydraulic data (Duty point)

Flow
Head
Shaft power P_2
Hydraulic efficiency
NPSH
Impeller size: 180

Product data

Glanded standard pump
Atmos GIGA-N 100/160-7.5/4/6
Max. operating pressure: 1,600 kPa
Fluid temperature: -20 °C ... +140 °C
Max. ambient temperature: 40 °C
Minimum efficiency index (MEI): ≥ 0.4

Motordata per Motor/Pump

Motor efficiency level: IE3
Mains connection: 3~ 380 V / 60 Hz
Permitted voltage tolerance: +10 %
Max. speed: 1,765 1/min
Rated power P_2 : 7.50 kW
Rated current: 15.60 A
Power factor: 0.8
Efficiency: 50% / 75% / 100% → 89.7/91.5/91.7%
Degree of protection: IP55
Insulation class: F
Motor protection: No

Fitting dimensions


Pipe connection on the suction side: DN 125, PN 16
Pipe connection (pressure side): DN 100, PN 16
Port to Port

Materials

Pump housing: 5.1301/EN-GJL-250
Impeller: EN-GJL-200
Lantern: 5.1301/EN-GJL-250
Shaft: 1.4021
Shaft seal: AQ1EGG

Information for order placements

Weight approx.: 249 kg
Item number



Dimensions

mm

A	125	H	521	L3	1,150
B2	490	H2	280	L4	1,170
B3	440	H3	303	S1	225
DN1	DN 125,	L	1,225	S4	24
DN2	DN 100,	L2	205	X	140



Contact
E-mail
Phone

Customer

Contact
E-mail
Phone

Hydraulic data

Glanded standard pump
Atmos GIGA-N 100/160-7.5/4/6

Project ID: Untitled project 2025-03-05 00:23:19.113


Project name
Installation location
Customer pos. No.

Date: 2025-03-05

Operating data

Rotational speed 1750 1/min	Frequency 60 Hz	Duty point Q =	H =	Suction port DN 125	Discharge port DN 100
---------------------------------------	---------------------------	--------------------------	------------	-------------------------------	---------------------------------

Power data referred to: Water; 20°C; 998.3kg/m³; 1.005mm²/s ±10 % tolerance with linear U/f frequency control



Pump curves in accordance with ISO 9906: 2012 3B

Contact
E-mail
Phone

Customer

Contact
E-mail
Phone


Dimensions

Glanded standard pump
Atmos GIGA-N 100/160-7.5/4/6

Project ID Untitled project 2025-03-05 00:23:19.113

Project name
Installation location
Customer pos. No.

Date 2025-03-05



Coupling with spacer

Suction side DN 125, PN 16
Discharge side DN 100, PN 16

Dimensions mm

Name	Value	Name	Value	Name	Value	Name	Value
A	125	H3	303	X	140		
B2	490	L	1,225				
B3	440	L2	205				
DN1	DN 125, PN 16	L3	1,150				
DN2	DN 100, PN 16	L4	1,170				
H	521	S1	225				
H2	280	S4	24				