

Technical data

Non-submersible sewage pump in monobloc design Rexa BLOC-V10.73-178DAH132M4

Project ID

Untitled project 2025-03-17 06:12:39.665


Project name

Installation location

Customer pos. No.

Date 2025-03-17

Duty chart



Requested data

Flow	
Head	
Media	Water 100 %
Fluid temperature	20.00 °C
Density	998.30 kg/m³
Kin. viscosity	1.00 mm²/s

Hydraulic data (Duty point)

Flow
Head
Shaft power P2
Total efficiency

Product data

Non-submersible sewage pump in monobloc design	
Rexa BLOC-V10.73-178DAH132M4	
Max. operating pressure	80 kPa
Fluid temperature	3 °C ... +70 °C
Max. ambient temperature	40 °C
Impeller type	Vortex impeller
Free ball passage	100 mm

Motordata per Motor/Pump

Type of motor	TEFC
Efficiency classification	IE3
Mains connection	3~ 400 V / 50 Hz
Permitted voltage tolerance	+/-10 %
Nominal speed	1,461 1/min
Rated power P2	7.50 kW
Power input P1	8.3 kW
Rated current	14.20 A
Activation type	Direct On Line (DOL)
Degree of protection	IP55
Motor protection	No
Insulation class	F

Fitting dimensions

Pipe connection on the suction side	DN 100, PN 10
Pipe connection (pressure side)	DN 100, PN 10

Materials

Pump housing	5.1301/EN-GJL-250
Impeller	5.1301/EN-GJL-250
Shaft	1.4021
Shaft seal	Q1Q1VGG
Gasket material	FKM
Motor housing	5.1301/EN-GJL-250

Information for order placements

Weight approx.	182 kg
Item number	6097844