

Technical data

Glanded monobloc pump Atmos BST 50/200-11/2-V2

Project ID

Untitled project 2025-03-01 17:12:44.130


Project name

Installation location

Customer pos. No.

Date 2025-03-01

Duty chart



Requested data

Flow	
Head	
Media	Water 100 %
Fluid temperature	20.00 °C
Density	998.30 kg/m ³
Kin. viscosity	1.00 mm ² /s

Hydraulic data (Duty point)

Flow	
Head	
Shaft power P2	
Hydraulic efficiency	
NPSH	
Impeller size	200

Product data

Glanded monobloc pump	
Atmos BST 50/200-11/2-V2	
Max. operating pressure	1,000 kPa
Fluid temperature	-20 °C ... +120 °C
Max. ambient temperature	50 °C
Minimum efficiency index (MEI)	≥ 0.4

Motordata per Motor/Pump

Motor efficiency level	IE3
Mains connection	3~ 400 V / 50 Hz
Permitted voltage tolerance	+6 %
Max. speed	2,900 1/min
Rated power P2	11.00 kW
Rated current	19.60 A
Power factor	0.89
Efficiency	50% / 75% / 100%
Degree of protection	IP55
Insulation class	F
Motor protection	

Fitting dimensions


Pipe connection on the suction side	DN 65, PN 16
Pipe connection (pressure side)	DN 50, PN 16
Port to Port	

Materials

Pump housing	1.4301
Impeller	1.4301
Shaft	1.4301
Shaft seal	B3Q1EF

Information for order placements

Weight approx.	
Item number	9187078



Dimensions

mm

A	100	B2	20	E	298	L1	140
A1	18	B3	20	F	615	L2	216
A2	18	dL	18	H	360	M1	70
A3	15	DN1	DN 65, P	H1	160	n1	212
B1	20	DN2	DN 50, P	H2	182	Ø k	145

Hydraulic data

Glanded monobloc pump
Atmos BST 50/200-11/2-V2

Project ID

Untitled project 2025-03-01 17:12:44.130

Project name


Installation location

Customer pos. No.

Date 2025-03-01

Operating data

Rotational speed	Frequency	Duty point		Suction port	Discharge port
2923 1/min	50 Hz	Q =	H =	DN 65	DN 50



Dimensions

Glanded monobloc pump
Atmos BST 50/200-11/2-V2

Project ID


Untitled project 2025-03-01 17:12:44.130

Project name

Installation location

Customer pos. No.

Date 2025-03-01



Standard

Suction side DN 65, PN 16

Discharge side DN 50, PN 16

Dimensions mm

Name	Value	Name	Value	Name	Value	Name	Value
A	100	dL	18	H2	182	Ø D	185
A1	18	DN1	DN 65, PN 16	L1	140		
A2	18	DN2	DN 50, PN 16	L2	216		
A3	15	E	298	M1	70		
B1	20	F	615	n1	212		
B2	20	H	360	Ø k	145		
B3	20	H1	160	Ø d	108		