

Customer


Technical data

High-pressure multistage centrifugal pump Helix V 611-1/25/E/KS/460-60

Project ID: Untitled project 2025-03-05 07:27:14.016

Project name
Installation location
Customer pos. No.

Date: 2025-03-05



Requested data

Flow
Head
Media: Water 100 %
Fluid temperature: 20.00 °C
Density: 998.30 kg/m³
Kin. viscosity: 1.00 mm²/s

Hydraulic data (Duty point)

Flow
Head
Shaft power P2
Hydraulic efficiency
NPSH

Product data

High-pressure multistage centrifugal pump
Helix V 611-1/25/E/KS/460-60
Max. operating pressure: 2,500 kPa
Inlet pressure max.: 10 bar
Fluid temperature: -30 °C ... +120 °C
Max. ambient temperature: 50 °C
Minimum efficiency index (MEI)

Motordata per Motor/Pump

Motor efficiency level
Mains connection: 3~ 400 V / 60 Hz
Permitted voltage tolerance: +10 %
Max. speed: 2,935 1/min
Rated power P2: 4.00 kW
Rated current: 7.90 A
Power factor: 0.84
Service factor: 1.15
Efficiency: 50% / 75% / 100% → 86/88/88.1 %
Degree of protection: IP55
Insulation class
Motor protection: PTC

Fitting dimensions

Pipe connection on the suction side: DN 32, PN 25
Pipe connection (pressure side): DN 32, PN 25

Materials

Pump housing: 1.4301
Impeller: 1.4307
Shaft: 1.4301
Shaft seal: BQ7EGG
Gasket material: EPDM

Information for order placements


Weight approx.: 55 kg
Item number: 4192434

ISO 9906: 2012 3B

Dimensions

H: 1,15
H2: 816
X: 155

mm



PN25

