

Customer

Technical data


Glanded standard twin-head pump DL 32/170-4/2

Project ID: Untitled project 2025-03-02 22:43:52.587

Project name
Installation location
Customer pos. No.

Date: 2025-03-02

Duty chart



Requested data

Flow	
Head	
Media	Water 100 %
Fluid temperature	20.00 °C
Density	998.30 kg/m ³
Kin. viscosity	1.00 mm ² /s

Hydraulic data (Duty point)

Flow	
Head	
Shaft power P ₂	
Hydraulic efficiency	
NPSH	

Product data

Glanded standard twin-head pump DL 32/170-4/2	
Max. operating pressure	1,600 kPa
Fluid temperature	-20 °C ... +140 °C
Max. ambient temperature	40 °C
Minimum efficiency index (MEI)	≥ 0.4

Motordata per Motor/Pump

Motor efficiency level	IE3
Mains connection	3~ 400 V / 50 Hz
Permitted voltage tolerance	+/- 10 %
Rated speed	2,900 1/min
Rated power P ₂	4.00 kW
Rated current	7.96 A
Power factor	0.83
Efficiency	50% / 75% / 100% 85.7/ 87.5/ 88.1%
Degree of protection	IP55
Insulation class	F
Motor protection	No

Fitting dimensions

Pipe connection on the suction side	DN 32, PN 16
Pipe connection (pressure side)	DN 32, PN 16
Port to Port	320 mm

Materials

Pump housing	5.1301/EN-GJL-250
Impeller	EN-GJL-200
Lantern	5.1301/EN-GJL-250
Shaft	1.4122
Shaft seal	AQ1EGG

Information for order placements

Weight approx.	135 kg
Item number	2121015

