



Contact  
E-mail  
Phone

Customer

Contact  
E-mail  
Phone

## Technical data

### KS 37ZH With motor F 17.1-2/8

Project ID                      Untitled project 2025-03-30 11:56:43.919  
Project name  
Installation location  
Customer pos. No.

Date    2025-03-30

#### Pump

Pump type	KS 37ZH
Installation type	Transportable
Free passage	6 mm
Nominal speed	2900
Rated frequency	50 Hz
Impeller type	Multi-channel
Impeller construction	Closed

#### Impeller Ø

max. possible	175 mm
min. possible	175 mm
standard	175
designed	175 mm

#### Suction port

Rated diameter	
Pressure rating	
Standard	

#### Discharge port

Rated diameter	G4
Pressure rating	PN10
Standard	EMU-D

#### Weights

Weight	max. 9 kg
Weight of motor	47 kg
Weight of unit	max. 56 kg

#### Materials

Pump housing	EN-GJL-250
Stationary wear ring	EN-GJS-500-7
Impeller	EN-GJS-500-7
Motor housing	G-Al Si12

#### Motor

Motor name	F 17.1-2/8
Number of poles	2
Rated power	3.85 kW
Rated speed	2860 1/min
Power input with rated power	5.1 kW
Rated voltage	400 ~3 V
Current input with rated power	8.3 A
Efficiency with rated power	76 %
cos phi with rated power	0.88
cos phi with starting	
Rated frequency	50 Hz
Operation type wet	S1
Operation type dry	S1
Starting current, direct starting	45.5 A
Starting current, star-delta	15.2 A
Starting torque	28 Nm
Inertia moment	0.0041 kg m <sup>2</sup>
Degree of protection	IP 68
Sel. explosion protection	
Ex-designation	
Ex-number	
Motor connection cable	4x1,5 NSSHÖU
Max. fluid temperature	40 °C
Starts per hour max.	15

#### Duty point data

Volume flow	
Head	
Shaft power P <sub>2</sub>	
Hydr. efficiency η <sub>hyd.</sub>	
Power input P <sub>1</sub>	
Fluid	Water
Required pump NPSH	
Rotational speed	2,868 1/min
Total efficiency	$= \frac{P_2 * \text{Hydr. efficiency } \eta_{\text{hyd.}}}{P_1}$

#### Weights

Submersible contractor's pump as single stage block unit for stationary, vertical installation, for pumping muddy water which does not attack the pump materials neither chemically nor mechanically.

Service friendly design of the unit by separate pump and motor.

Pumping values to be guaranteed according to ISO 9906 Annex A



Contact  
E-mail  
Phone

Customer


Contact  
E-mail  
Phone

## Performance curves

**KS 37ZH**  
With motor  
**F 17.1-2/8**

Project ID                      Untitled project 2025-03-30 11:56:43.919  
Project name  
Installation location  
Customer pos. No.

Date    2025-03-30



Power data referred to:                      Water; 20°C; 998.3kg/m<sup>3</sup>; 1.005mm<sup>2</sup>/s  
Tolerance as per ISO 9906 / Annex A.2

### Pump

Impeller Ø                      designed    175 mm  
Nominal speed                      2,860 1/min  
Frequency                              50 Hz  
Impeller type                              Multi-channel

### Motor

Rated power                              3.85 kW  
Sel. explosion protection

### Duty point data

Volume flow  
Head  
Shaft power P2  
Hydr. efficiency η hyd.  
Power input P1  
Required pump NPSH  
Rotational speed                              2868 1/min

Contact  
E-mail  
Phone

Customer


Contact  
E-mail  
Phone

## Dimensions

**KS 37ZH**  
With motor  
**F 17.1-2/8**

Project ID                      Untitled project 2025-03-30 11:56:43.919  
Project name  
Installation location  
Customer pos. No.

Date    2025-03-30



### Dimensions

Name	Value	Name	Value
a	644 mm		
d	295 mm		
e	295 mm		
i	573 mm		
m	588 mm		
n	758 mm		
p	712 mm		
r	730 mm		
s	739 mm		

### Connections

Suction port	
Discharge port	G4 PN10