

5SV14F0406T/D

Technical data

Company name
Contact
Phone number
e-mail address

Operating data

Pump type	Single head pump	Fluid	Water
Available system NPSH	ft 0	Operating temperature t A	°F 39.2
Nominal flow	US g.p.m. 0	pH-value at t A	7
Nominal head	ft 0	Density at t A	lb/ft³ 62.4
Static head	ft 0	Kin. viscosity at t A	ft²/s 1.689E-5
Inlet pressure	psi 0	Vapor pressure at t A	psi 14.5
Environmental temperature	°F 68	Solids	0
		Altitude	ft 0

Pump data

Make	Lowara	Nominal	US g.p.m. ()
Speed	rpm 3500	Flow	Max- US g.p.m. 44
Number of stages	14		Min- US g.p.m.
Max. casing pressure	psi		Nominal ft
Max. working pressure	psi 218.3	Head	at Qmax ft 239.2
Head H(Q=0)	ft 500		at Qmin ft 503.3
Weight	lb 117	Shaft power	hp ()
	Max. inch 3	Max. shaft power	hp 4.5
Impeller R	designed inch 3	Efficiency	%
	Min. inch 3	NPSH 3%	ft

Pump Materials

Pump body	Stainless steel / AISI 304
Impeller	Stainless steel / AISI 304
Diffuser	Stainless steel / AISI 304
Outer sleeve	Stainless steel / AISI 304
Shaft	Stainless steel / AISI 304
Adapter	Cast iron
Base	Aluminium
Coupling	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 304
Tie rods	Galvanized steel
Wear ring	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	220 V	Speed	3510 rpm	Insulation class	F
Specific design	IE3 3ph Flange Motor			Frame size	112 M	Colour	RAL 5010
Type	PLM 112R B14 4 kW						
Rated power	5.3641 hp	Degree of protection	IP55				
Electric current	13.6 A						

Remarks:

5SV14F0406T/D

Performance curve

Company name
Contact
Phone number
e-mail address


Hydraulic data

Operating Data Specification		Hydraulic data (duty point)	Impeller design	
Flow	0 US g.p.m.	Flow	Impeller R	3 inch
Head	0 ft	Head	Frequency	60 Hz
Static head	0 ft	MEI ---	Speed	3500 rpm

Power datas referred to:

Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s

Performance according to ISO 9906:2012 – Grade 3B



Project Xylect-20142397
Block 5SV14F0406T/D

Created by
Created on 12/28/2024

Last update 12/28/2024
Page 2 / 3

Program version
75.0 - 06/12/2024 (Build 274)

Data version
15/12/2024 18:59


User group(s)
Xylem: United Kingdom - EXT

5SV14F0406T/D

Dimensions

Company name
Contact
Phone number
e-mail address

Drawing



Dimensions inch

Electrical and dimensional data refer to IE3 motor

D1	7 ³ / ₄	M	6 ¹ / ₁₆			Weight
D2	6 ⁵ / ₁₆					100 lb
L1	23 ⁹ / ₁₆					
L2	12 ⁹ / ₁₆					
L3	23 ⁹ / ₁₆					
L4	16 ⁷ / ₁₆					
L5	22 ⁹ / ₁₆					