

LNES 50-200/15/P46PCS4

Technical data

Company name
Contact
Phone number
e-mail address

Operating data

1	Pumpe type	Single head pump	Fluid	Water
2	No. of pumps	1	Operating temperature t A	°F 39.2
3	Nominal flow	US g.p.m. 0	Max / Min Operating Temperature mech. Seal	°F 120 / -25
4	Nominal head	ft 0	pH-value at t A	7
5	Static head	ft 0	Density at t A	lb/ft³ 62.4
6	Inlet pressure	psi 0	Kin. viscosity at t A	ft²/s 1.689E-5
7	Environmental temperature	°F 68	Vapor pressure at t A	psi 14.5
8	Available system NPSH	ft 0	Altitude	0

Pump data

9	Lubrication	Standard, Grease lubrication [Std]		
10	Execution			
11	Design	In-line	Impeller Ø	Max. inch 7 13/16
12	Operating speed	1750 rpm		designed inch 6 15/16
13	Suction nozzle	DN 50 / PN 16 / EN1092-2		Min. inch 6 15/16
14	Discharge nozzle	DN 50 / PN 16 / EN1092-2	Flow	Nominal US g.p.m.
15	Max. casing pressure	psi		Max- US g.p.m. 145.3
16	Max. working pressure	psi 20.1		Min- US g.p.m. 35.2
17	Impeller type	Radial impeller	Head	Nominal ft
18	Head H(Q=0)	ft 46		at Qmax ft 24.8
19	Max. shaft power	hp 2		at Qmin ft 46.9
20	Pump weight	kg	Shaft power	hp
21	Total weight	lb 145.5	Efficiency	%
			NPSH 3%	ft

Materials

22	Pump		Shaft Seal	
23	Volute Casing	Cast iron	Single mechanical seal, without shaft sleeve	
24	Casing Cover	Cast iron	eMG12 - Ø22mm	BQ7EGG-WA
25	Impeller	Stainless steel / AISI 304	Mechanical seal diameter	7/8 inch
26	Stub shaft	Stainless steel / AISI 316L	1. Rotating ring	Carbon graphite resin impregnated
27	Wear ring	Stainless steel / AISI 304	2. Stationary ring	SiC, silicon carbide, sintered press.less
28	Impeller lock nut and washer	Stainless steel / AISI 304	3. Secondary seal	Ethylene propylene rubber (EPDM)
29	Impeller key	Stainless steel / AISI 316L	4. Springs	CrNiMo - Steel
30	Fill and drain plugs	Nickel-plated brass	5. Others	EPDM - WRAS
31			Gaskets of the pump	Ethylene propylene rubber (EPDM)
32				
33				
34				
35				
36				
37				
38				
39				
40				
41				

Motor data

Electrical and dimensional data refer to IE3 motor

42	Manufacturer	Lowara	
43	Specific design	IE3 3ph Flange Motor - Premium Efficiency	
44	Type	PLM 90 B5 1,5 kW	
45	Rated power	2.0115 hp	Rated current 6.34 A
46	Nominal speed	1734 rpm	Rated voltage 220 V
47	Frame size	90	Service factor 1
48	Weight	lb 49.8	Degree of protection IP55

Remarks

49	
50	
50	
52	

Project	Xylect-20070985	Created by		Last update	1/19/2025
Block	LNES 50-200/185/P26PCS4	Created on	1/19/2025		

LNES 50-200/15/P46PCS4

Performance curve

Company name
Contact
Phone number
e-mail address


	Ø mm	Pump capacity Operating range			Pump head H(Q=0)		Shaft power P2			Frequency		Hz
		Min. US g.p.m.	Max. US g.p.m.	Max. η US g.p.m.	Max. η ft	Max. η ft	P2(Q=0) hp	Max. hp	Max. η hp	Operating speed rpm	Nominal flow US g.p.m.	
actual	6 15/16	35.2	137	96.9	46.4	40.2		2.05	1.73	1750	0	60
Min.	0	/	/	96.9	46.4	40.2		/	1.73		0	
Max.	7 13/16	/	/	166	112	92.5		/	6.24		0	

Power datas referred to:

hydr. Performance acceptance acc. To EN ISO 9906 Class Grade 3B

Water [100%] ; 39.2°F; 62.4lb/ft³; 1.69E-5ft²/s

MEI: N.A - according to Ecodesign Directive 2009/125/EC and Regulation (EU) No.547/2012



LNES 50-200/15/P46PCS4


Dimensions

Company name
Contact
Phone number
e-mail address

Rigid coupling

PLM 90 B5 1,5 kW

Electrical and dimensional data refer to IE3 motor



Dimensions [inch]


AD	9 ⁷ / ₁₆		
b1	6 ⁵ / ₈		
Bmax	13 ¹ / ₄		
DNd	1 ¹⁵ / ₁₆		
DNs	1 ¹⁵ / ₁₆		
e	4 ³ / ₈		
f	6 ¹ / ₈		
H	17 ⁵ / ₁₆		
h1	8 ¹¹ / ₁₆		
h2	8 ¹¹ / ₁₆		
L	22 ³ / ₁₆		
p	6 ⁷ / ₈		
x	4 ¹ / ₄		

Weight

Total weight	66 kg
--------------	-------

Connections

Suction nozzle	Discharge nozzle
DN 50	DN 50
PN 16	PN 16
EN1092-2	EN1092-2
C	13 ¹ / ₁₆
D	6 ¹ / ₂
df	3 ⁷ / ₈
DN	1 ¹⁵ / ₁₆
K	4 ¹⁵ / ₁₆
L	4 x 19



Value C, D may vary from Standard

Dimensions and weight without obligation

Project	Xylect-20070985	Created by		Last update	1/19/2025
Block	LNES 50-200/185/P26PCS4	Created on	1/19/2025		