

LNES 80-200/185/P25VCC4

Technical data

Company name
Contact
Phone number
e-mail address

Operating data

1	Pumpe type	Single head pump	Fluid	Water
2	No. of pumps	1	Operating temperature t A	°C 4
3	Nominal flow	m³/h 0	Max / Min Operating Temperature mech. Seal	°C 120 / -25
4	Nominal head	m 0	pH-value at t A	7
5	Static head	m 0	Density at t A	kg/m³ 1000
6	Inlet pressure	kPa 0	Kin. viscosity at t A	mm²/s 1.569
7	Environmental temperature	°C 20	Vapor pressure at t A	kPa 100
8	Available system NPSH	m 0	Altitude	0

Pump data

9	Lubrication	Standard, Grease lubrication [Std]		
10	Execution			
11	Design	In-line	Impeller Ø	Max. mm 220
12	Operating speed	2900 rpm		designed mm 189
13	Suction nozzle	DN 80 / PN 16 / EN1092-2		Min. mm 165
14	Discharge nozzle	DN 80 / PN 16 / EN1092-2	Flow	Nominal m³/h
15	Max. casing pressure	kPa		Max- m³/h 139.5
16	Max. working pressure	kPa 486.6		Min- m³/h 30.3
17	Impeller type	Radial impeller	Head	Nominal m
18	Head H(Q=0)	m 50		at Qmax m 28.5
19	Max. shaft power	kW 17		at Qmin m 50.1
20	Pump weight	kg	Shaft power	kW
21	Total weight	kg 168.2	Efficiency	%
			NPSH 3%	m

Materials

22	Pump		Shaft Seal	
23	Volute Casing	Cast iron	Single mechanical seal, without shaft sleeve	
24	Casing Cover	Cast iron	eMG12 - Ø28mm	BQ7EGG-WA
25	Impeller	Cast iron / ASTM Class 30	Mechanical seal diameter	28 mm
26	Stub shaft	Stainless steel / AISI 431	1. Rotating ring	Carbon graphite resin impregnated
27	Wear ring	Stainless steel / AISI 304	2. Stationary ring	SiC, silicon carbide, sintered press.less
28	Impeller Nut	Stainless steel	3. Secondary seal	Ethylene propylene rubber (EPDM)
29	Impeller washer	Stainless steel	4. Springs	CrNiMo - Steel
30	Impeller key	Stainless steel / AISI 316Ti	5. Others	EPDM - WRAS
31	PLUG	Stainless steel / AISI 316Ti	Gaskets of the pump	Ethylene propylene rubber (EPDM)
32	GASKET	Asbestos-free synthetic fiber AFM34		
33				
34				
35				
36				
37				
38				
39				
40				
41				

Motor data

Electrical and dimensional data refer to IE3 motor

42	Manufacturer	Lowara		
43	Specific design	IE3 3ph Flange Motor - Premium Efficiency		
44	Type	PLM 160 B5 18,5 kW		
45	Rated power	18.5 kW	Rated current	32.7 A
46	Nominal speed	2940 rpm	Rated voltage	400 V
47	Frame size	160	Service factor	1
48	Weight	kg 110.0	Degree of protection	IP55

Remarks

49	
50	
50	
52	

Project	Xylect-20128214	Created by		Last update	12/21/2024
Block	LNES 80-200/300/L25VCC4	Created on	12/21/2024		

LNES 80-200/185/P25VCC4

Performance curve

Company name
Contact
Phone number
e-mail address


	Ø mm	Pump capacity Operating range Min. Max. η m³/h m³/h m³/h			Pump head H(Q=0) η m m		Shaft power P2 P2(Q=0) Max. η kW kW kW			Frequency Hz 50	
		Min.	Max.	Max.	H(Q=0)	η	P2(Q=0)	Max.	η	Operating speed	rpm
actual	189	30.3	140	97.4	49.6	41.5	17	14.8		Nominal flow	m³/h
Min.	0	/	/	79.5	36.2	30	/	9.01		Nominal head	m
Max.	220	/	/	119	69.1	58.6	/	25.2		Inlet pressure	kPa
										Static head	m

Power datas referred to:

hydr. Performance acceptance acc. To EN ISO 9906 Class Grade 3B

Water [100%] ; 4°C; 1000kg/m³; 1.57mm²/s

MEI: N.A - according to Ecodesign Directive 2009/125/EC and Regulation (EU) No.547/2012



LNES 80-200/185/P25VCC4


Dimensions

Company name
Contact
Phone number
e-mail address

Rigid coupling

PLM 160 B5 18,5 kW

Electrical and dimensional data refer to IE3 motor



Dimensions [mm]


AD	240
b1	185
Bmax	353
DNd	80
DNs	80
e	132
f	240
H	500
h1	265
h2	235
L	866
p	313
x	130

Weight

Total weight	168.2 kg
--------------	----------

Connections

Suction nozzle	Discharge nozzle
DN 80	DN 80
PN 16	PN 16
EN1092-2	EN1092-2
C	22
D	200
df	132
DN	80
K	160
L	8 x 19



Value C, D may vary from Standard

Dimensions and weight without obligation

Project	Xylect-20128214
Block	LNES 80-200/300/L25VCC4

Created by	
Created on	12/21/2024

Last update	12/21/2024
-------------	------------