

NSCF 65-315/150/P45VCC4

Technical data

Company name
Contact
Phone number
e-mail address

Operating data

1	Pumpe type	Single head pump	Fluid	Water, pure
2	No. of pumps	1	Operating temperature t A	°C 4
3	Nominal flow	m³/h 0	Max / Min Operating Temperature mech. Seal	°C 120 / -25
4	Nominal head	m 0	pH-value at t A	7
5	Static head	m 0	Density at t A	kg/m³ 1000
6	Inlet pressure	kPa 0	Kin. viscosity at t A	mm²/s 1.569
7	Environmental temperature	°C 20	Vapor pressure at t A	kPa 100
8	Available system NPSH	m 0	Altitude	0

Pump data

9	Lubrication	Standard, Grease lubrication [Std]								
10	Execution	Standard coupling				Impeller Ø	Max.	mm	334	
11	Design	Horizontal					designed	mm	334	
12	Operating speed	1465 rpm		Stages 1			Min.	mm	260	
13	Suction nozzle	DN80 /		PN10/16 /		EN1092-2		Nominal	m³/h	
14	Discharge nozzle	DN65 /		PN10/16 /		EN1092-2		Max-	m³/h	130
15	Max. casing pressure	kPa						Min-	m³/h	14
16	Max. working pressure	kPa		380.3				Nominal	m	
17	Impeller type			Radial impeller		Head	at Qmax	m	20	
18	Head H(Q=0)	m		39			at Qmin	m	38.8	
19	Max. shaft power	kW		12.4		Shaft power		kW		
20	Pump weight	kg		102		Efficiency		%		
21	Total weight	kg		343.2		NPSH 3%		m		

Materials

22	Pump		Shaft Seal	
23	Volute Casing	Cast Iron, EN 1561 - GJL-250, ASTM Class 35	Single mechanical seal, without shaft sleeve	
24	Impeller	Cast Iron, EN 1561 - GJL-200, ASTM Class 30	eMG12 - Ø38mm	BQ7EGG-WA
25	Casing Cover	Cast Iron, EN 1561 - GJL-250, ASTM Class 35	Mechanical seal diameter	38 mm
26	Shaft	Stainless steel, 1.4057, AISI 431	1. Rotating ring	Carbon graphite resin impregnated
27	Wear ring	Stainless steel, 1.4301, AISI 304	2. Stationary ring	SiC, silicon carbide, sintered press.less
28	Impeller lock nut and washer	A4 (1.4401)	3. Secondary seal	Ethylene propylene rubber (EPDM)
29	Impeller key	Stainless steel, 1.4571, AISI 316Ti	4. Springs	CrNiMo - Steel
30	Fill and drain plugs	Galv anized carbon steel, EN 10277-3, AISI 1213 / 1215	5. Others	EPDM - WRAS
31	Bearing bracket	Cast Iron, EN 1561 - GJL-250, ASTM Class 35	Gaskets of the pump	Ethylene propylene rubber (EPDM)
32				
33				
34				
35				
36				
37				
38				
39				
40				
41				

Motor data

Electrical and dimensional data refer to IE3 motor

Coupling

42	Manufacturer	Lowara	Manufacturer	Flender
43	Specific design	IE3 3ph Surface Motor - Premium Efficiency	Series	Standard Coupling - N-EUPEX - Type B
44	Type	PLM 160 B3 15 kW	Shaft diameter	Pump 32 mm Motor 42 mm
45	Rated power	15 kW	Rated current	30.7 A
46	Nominal speed	1465 rpm	Rated voltage	400 V
47	Frame size	160	Service factor	1
48	Weight	kg 127.4	Degree of protection	IP55
			Coupling protection	GR.COUPLGUARD ES32-190-16 A4 1.8 kg

Base plate

49	Name	BASEFRAME_NSC80-2_C00
50	Weight	kg 108.7

Project	Xylect-20101351	Created by		Last update	12/15/2024
Block	NSCF 65-315/900/L25VCC4 E4	Created on	12/15/2024		

NSCF 65-315/150/P45VCC4

Performance curve

Company name
Contact
Phone number
e-mail address


	Ø mm	Pump capacity Operating range			Pump head η		Shaft power P2 η			Frequency		Hz
		Min. m³/h	Max. m³/h	Max. m³/h	H(Q=0) m	Max. m	P2(Q=0) kW	Max. kW	Max. kW	Operating speed	rpm	
actual	334	14	130	81.8	38.8	32.7		12.4	10.1	Nominal flow	m³/h	0
Min.	0	/	/	61.2	22.7	18.7		/	4.57	Nominal head	m	0
Max.	334	/	/	81.8	38.8	32.7		/	10.1	Inlet pressure	kPa	0
										Static head	m	0

Power datas referred to:

hydr. Performance acceptance acc. To EN ISO 9906 Class Grade 3B

Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s

MEI: >=0,70 - according to Ecodesign Directive 2009/125/EC and Regulation (EU) No.547/2012






NSCF 65-315/150/P45VCC4

Dimensions

Company name
Contact
Phone number
e-mail address

Frame mounted
Standard coupling
PLM 160 B3 15 kW

Electrical and dimensional data refer to IE3 motor



Value C, D may vary from Standard

Dimensions [mm]

a	125
a1	110
b2	670
b3	630
CTO	0
DNd	65
DNs	80
E	3/8"
F	3/8"
f	470
Guard	194
h	365
h2	280
Hmax	645
L	1203
L1	1330
L2	110
L3	1110
PM1	1/4"
s	6xØ19
Trim	0
Volumen	0.51988

Weight

Total weight	343.2 kg
--------------	----------

Connections

Suction nozzle		Discharge nozzle	
DN80		DN65	
PN10/16		PN10/16	
EN1092-2		EN1092-2	
C	22	C	20
D	200	D	185
d1	132	d1	118
K	160	K	145
L	19	L	19
z	8	z	4

Dimensions and weight without obligation

Project Xylect-20101351
Block NSCF 65-315/900/L25VCC4 E4

Created by
Created on 12/15/2024

Last update 12/15/2024