

CO 500/15/D


Technical data

Company name
Contact
Phone number
e-mail address

Performance according to ISO 9906:2012 – Grade 3B

Power datas referred to:

Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s



Operating Data Specification

Flow	0 m³/h
Head	0 m

Hydraulic data (duty point)

Flow	
Head	
Max. shaft power	1.53 kW

Pump data

Make	Lowara
Type	CO 500/15/D
Open impeller centrifugal pump with threaded connections	
Speed	2900rpm
Head H(Q=0)	16 m
Suction side	
Discharge side	
Types of installation	Monobloc
Weight	21 kg

Materials / seals

Pump body	Stainless steel
Impeller	Stainless steel
SEAL HOUSING	Stainless steel
Shaft extension	Stainless steel

Shaft Seal

Rotating Assembly	V-Ceramic
Fixed Assembly	B-Resin impregnated carbon
Elastomers	V-FKM (FPM)
Springs	G-AISI 316
Other Components	G-AISI 316

Motor data

Rated power P2	1.5 kW	Nom. Speed	2870 rpm
Frequency	50	Phase	3~
Rated voltage	230 V	Rated current	5.49 A
Protection class	IP55	Insulation class	F
Permitted voltage tolerance +/- 10%			

Dimensions mm

D	174		
DNA	Rp 2		
DNM	Rp 1½		
H2	245		
L	429		
L1	172		
L2	147.5		

Note:

